Smart Card Personalization in a Multistation Environment

Field of the Invention

The present invention relates generally to data storage devices and more

5   specifically to the control of smart card personalization in a multistation environment.

Background of the Invention

Increasing numbers of organizations which issue transaction cards to their users,

customers, or employees require cards tailored to meet the requirements of their

10   particular service or application. These organizations also want the cards to contain

data about the cardholder. Existing transaction cards encode such data in a magnetic

stripe on the back of the card but the amount of data that can be held by a magnetic

stripe is limited. A new type of transaction card embeds a microprocessor computer

chip in the plastic of the card to greatly increase the card's data storage capacity.

15   Additionally, sophisticated card applications specific to the card issuer can execute in

certain varieties of the chips, and the chip may also contain a type of operating system.

Transaction cards with embedded chips are referred to in the industry as portable

programmed data carriers, more commonly called "smart cards." The chip in a smart

card is generally programmed with initialization and/or personalization data at the same

20   time as the surface of the card is being embossed and/or printed.

The initialization data comprises three major types of information: application

data, security data, and printed data. The application data is common to all cards for a

1

given card application and includes application program code and variables. The

security data prevents fraudulent use of the card and is usually provided in the form of

"secure keys." Printed data, such as a logo, bar codes, and various types of numerical

information, are placed on the surface of the card. Some or all of the same data can also

5   be embossed on the surface. Optical technology also can be employed to make part or

all of the surface of the card into a storage medium with data accessible by an

appropriate optical reader.

Smart cards are also programmed with information specific to an individual

cardholder through a process called "personalization." The personalization information

10   for a smart card is similar to the personalization information currently contained on

non-smart cards, such as the cardholder's name, account number, card expiration date,

and a photograph. Because of its increased storage capacity, the chip in a smart card

can contain additional data beyond the basic information on the standard transaction

card including a graphical representation of the individual's signature, data defining the

15   types of service the cardholder is entitled to, and account limits for those services.

Current systems from performing smart card initialization and/or personalization

include a controller or a personal computer which is connected to a personalization

station. All of the smart card programming data required for the personalization process

is sent from the controller or personal computer to the personalization station which

20   programs the smart card. An application running on the personalization station controls

the programming of the smart card. Many current personalization stations have a

limited capacity to handle the increasingly sophisticated personalization process as the

size and functionality of smart card computer chips increase. Such limitations include the memory, processing capacity, and buffer size of the personalization stations.

In addition, personalization stations may require access to external resources which provide security services or access to card data. The external resources, particularly the security services, are expensive infrastructures to repeat for each personalization station. Also, communication between the personalization station and the external resource is limited by the speed of the communication link between them. In addition, the application development environment available on the personalization stations is often unique and lacking in development tools.

Therefore, there is a need for a personalization system which overcomes the limitations on memory capacity and processing flexibility of current personalization stations. There is also a need for a personalization system which can share external resources between multiple personalization stations.

Summary of the Invention

The above-identified shortcomings as well as other shortcomings are addressed by the present invention, which will be understood by reading and studying the following specification. The invention is a computerized system for controlling programming of portable programmed data carriers across a plurality of personalization stations. The system includes a personalization server interface for acquiring services from one or more resources, transferring card information to one of the personalization stations and controlling the programming of the portable programmed data carrier. The

3

system also includes a personalization station interface for receiving the card

information from the personalization server interface and for programming the portable

programmed data carrier.

The invention also described is a method of controlling programming of portable

5   programmed data carriers in a system having a plurality of ~~programming~~ *personalization* stations. The

method includes receiving one or more card objects from a card issuer management

system. The card objects consist of information for programming the portable

programmed data carriers. The method also includes receiving a programming request

from the ~~programming~~ *personalization* station and utilizing the card object to control the ~~programming~~ *personalization*

10   station as the ~~programming~~ *personalization* station programs the portable programmed data carrier.

Alternatively, the invention described is a computerized system which includes a

means for receiving one or more card objects from a card issuer management system.

The computerized system also includes a means for receiving a programming request

from the programming station and a means for utilizing the card object to control the

15   ~~programming~~ *personalization* station as the ~~programming~~ *personalization* station programs the portable programmed

data carrier.

The smart card personalization system uses a data structure comprising a data

field representing a card object containing information for programming a portable

programmed data carrier and an additional data field containing a unique card object

20   identifier for identifying the card object.

Therefore, the smart card personalization system of the present invention shares

external resources between multiple personalization stations. Other aspects and

4

advantages of the invention will become apparent by reference to the drawings and by reading the following detailed description.

Brief Description of the Drawings

5   Figure 1   is a block diagram representing an embodiment of a smart card issuing process that incorporates a smart card personalization server of the present invention.

Figure 2   is a functional block diagram of input and output connections for the embodiment of the smart personalization server of shown in Figure 1.

10   Figure 3   is a block diagram showing one embodiment of the smart card personalization software of the present invention.

Figure 4   is a high level flow chart for one embodiment of software which implements the functions of the smart card personalization server.

Description of the Embodiments

15

In the following detailed description of the embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to

20   practice the invention, and it is to be understood that other embodiments may be utilized and that structural, logical and electrical changes may be made without departing from the spirit and scope of the present inventions. The following detailed description is,

5

therefore, not to be taken in a limiting sense, and the scope of the present inventions is defined only by the appended claims.

The leading digit(s) of reference numbers appearing in the Figures usually corresponds to the Figure number, with the exception that identical components which

5   appear in multiple figures are identified by the same reference numbers.

The system of the present invention utilizes a personalization server to control smart card personalization in an environment having a plurality of personalization stations. The personalization server provides an interface to a plurality of card personalization stations and to external computing or data resources which normally are

10   not directly available to the card personalization stations or which are not cost efficient to replicate at each card personalization station.

The detailed description of this invention is divided into four sections. The first section provides an overview of one embodiment of a system for issuing smart cards which incorporates a smart card personalization server of the present invention. The

15   second section describes the functional specifications for the software components of the example embodiment of the smart card personalization system. The third section illustrates an example communication sequence between personalization station interface software and personalization server software for a smart card personalization process. The fourth section is a conclusion which includes a summary of the

20   advantages of the present invention.

Smart Card Personalization System Overview. Figure 1 illustrates components of a smart card issuing process that incorporates one embodiment of the

6

smart card personalization server of the present invention. The smart card

personalization server 100 receives card objects from a card issuer management system

150. A smart card personalization controller 120 receives, from the card issuer

management system 150, a card object identifier for each one of the card objects passed

5 to the smart card personalization server 100. The smart card personalization controller

120 routes each one of the card object identifiers to one of a plurality of personalization

stations 130. Each personalization station 130 uses the card object identifier to request

data and services from the smart card personalization server 100 in order to personalize

a smart card 160.

10 The card issuer management system 150 manages the cardholder data and

determines the type of card to issue, the card applications to embed in the card, and

what personalization equipment to use to issue the card for a particular cardholder.

The smart card personalization server 100 is illustrated in Figure 1 as a computer

executing personalization server software as further described below. The

15 personalization server software executes under an operating system such as Unix,

Windows 95©, or Windows NT©, and on industry-standard workstation and/or personal

computer hardware. As described below, the smart card personalization server 100

provides an interface to card personalization stations 130 and to external computing or

data resources 180.

20 The server 100 controls card printers, embossing devices, and integrated or

add-on smart card interface devices collectively represented in Figure 1 as a plurality of

personalization stations 130. Personalization stations 130 also represent such devices as

large volume card printer/embossers, small volume card printer/embossers, automatic

teller machines (ATMs), point of sale terminals, unattended kiosks, personal computers,

network computers, and on-line telecommunication devices. The physical connection

between the devices and the smart card personalization server 100 varies according to

5   the manufacturer and model of the device. Common industry standard connections

include serial RS232, SCSI (Small Computer System Interface), Ethernet, and serial

TTL (Transistor-Transistor Logic). In addition, some devices require a proprietary bus

connection.

The connections between the smart card personalization server 100 and the card

10   management system 150 and the stations 130 can also be implemented through standard

local area networks, wide area networks, dedicated phone lines, or other remote

communication infrastructure used to transfer data. Alternate connections will be

apparent to those skilled in the art and are within the scope of the invention.

Figure 2 is a block diagram of one embodiment of the smart card personalization

15   system illustrating the logical input and output connections for the smart card

personalization server 100. The cardholder data 202 input and maintained by the card

issuing organization contains information about each individual cardholder, such as

name, account number, card expiration date, and applicable services. The card issuer

management system 150 assembles the data necessary for each card personalization job.

20   The data for each job can be stored in a card object data store, such as a database, with

each card object 208 accessible by a unique card object identifier. A job can be, for

example, a logical grouping of similar card objects.

The card objects 208 contain, for example but not with limitation, data and commands for magnetic stripe encoding, embossing, printing, packaging and smart card personalization.   An example card object is shown below.

5

Card Object

EMB= "123456789", "Your Name", "1/1/1999"

ENC=%B123456789^ Y/Name^01011999?;123456789=01011999?

PIC=www.photos.com/YourName

SCRD=this_unique_card_object_identifier

10

The example card object begins with an emboss instruction "EMB" followed by the corresponding cardholder data to be embossed on the card. The second line in the example card object shown above is an encode instruction "ENC" followed by the ~~corresponding data to be~~ corresponding cardholder data to be encoded on the magnetic

15   strip of the card. The third line in the example card object is an instruction to print a picture on the card "PIC" followed by the location of the cardholder's picture. The fourth line in the example card object is a smart card portion of the card object "SCRD". The smart card portion of the card object 208 consists of the unique card object identifier.

20   The card issuer management system 150 passes the card object 208 to the smart card personalization server 100. The smart card personalization server 100 expects the personalization data to be in a particular format. Because the card object 208 is in a

format defined by the card issuer that often differs from the format(s) expected by the server 100, the card object 208 is translated by the server 100 when necessary. One method of translating the card object is described in U.S. Patent Application serial number 08/755,459 entitled "System and Apparatus for Smart Card Personalization", filed on November 22, 1996.

The smart card personalization server 100 provides an interface to external security services 204 and additional data sources 206 as needed to perform a smart card personalization job. The software program for the smart card personalization server 100 can be coupled to the data sources 206 through standard data query commands that provide access to the data stored in the data sources. The communication protocols between the software program for the smart card personalization server 100 and the external security services 204 and the data sources 206 vary depending upon the underlying data management system or security system employed.

The smart card personalization server 100 also provides an interface to each one of a plurality of card personalization stations 130. The smart card personalization controller 120 passes a card object identifier to one of the waiting personalization stations 130. The personalization station 130 presents the card object identifier to the server 100 in order to initiate access to the data services, security services or support services needed to complete the smart card personalization. Upon receiving the card object identifier from the personalization station 130, the smart card personalization server 100 translates the card object indicated by the card object identifier. The translation of the card object by the smart card personalization server 100 results in a

sequence of commands and/or data which are passed to the personalization station 130. The personalization station 130 passes the commands and data received from the server 100 directly to the smart card 160. An example process demonstrating how the server 100 controls the actual card programming is described below.

5   **Personalization Software Specifications.** Figure 3 is a block diagram showing one embodiment of the smart card personalization server 100 of Figure 2. The system of the present invention utilizes the personalization server 100 to control smart card personalization in an environment having a plurality of personalization stations 130 coupled to the personalization server 100. The personalization server 100 provides an

10   interface to card personalization stations 130 and to external computing or data resources 204, 206 as shown in Figure 2.

An application executing on a card issuer management system 150 prepares a card object 303 and assigns a card object identifier to each object. Information regarding the card objects is archived in a card object database 302 until called upon by

15   the personalization server 100 to personalize a smart card.

The personalization environment of the present invention comprises two complimentary software components. The first is personalization station interface software 304 which executes in a processor of the personalization station 130. The second is personalization server software 305 executing in a processor in the

20   personalization server 100 which processes the personalization card objects and utilizes both local and external resources.

A initialization process 306 initiates a personalization job by initiating the

11

personalization server 100 and optionally sending data, such as embossing or magnetic stripe encoding data, to the personalization station 130. The personalization server software 305 serves multiple card personalization processes 308. Each card personalization process 308 represents a personalization job occurring at one of the

5   personalization stations 130. Each card personalization process 308 is logically linked to one of the personalization stations 130.

The personalization station interface software 304 presents the unique card object identifier to the personalization server software 305 to initiate access to services available through the server software 305. The personalization server software 305

10   obtains all of the necessary job information as well as the data elements to be used in personalization of the smart card. The personalization station interface software 304 performs the card personalization utilizing the services available to it through the personalization server software 305 as required until personalization is complete. At completion of the job, the personalization station interface software 304 is notified by

15   the server software 305 of completion.

The services provided by the server software 305 include data services 312, security services 310 and support services 314. The data services 312 perform the acquisition of data for each personalization job and include any commonly available means of accessing data. The data services 312 retrieve data archived in the card object

20   data base 302 on the card issuer management system 150 as well as from additional external data sources as shown in Figure 2. The data can be in the form of files, databases, or data structures for example.

12

The security services 310 interface with a variety of different external sources which provide security functions. The security functions provided by the external sources include any commonly available means of securing information or limiting access to smart card chips until a required security condition is met. An example

5   security function utilizes one or more "secure keys" that are programmed into the chip to prevent fraudulent use of the card. The appropriate secure key data is obtained by the smart card personalization server software 305 from secure key records maintained by the card issuer or an external security source and then transferred to the personalization station interface software 304. The security services 310 also provide security functions

10   that can be used, for example, to ensure the integrity and secrecy of data during the transmission of data to and from the personalization station 130.

The support services 314 perform processing tasks that in prior systems were performed by the personalization station 130 or were unable to be performed at all due to the limitations of the personalization stations. The support services 314 include any

15   commonly used functions that can be shared between processes such as data conversions and validations for example. An example support service 314 is year 2000 date validation processing. An additional example of a support service 314 is formatting a ten digit string of numbers representing a telephone number so that the area code is in parentheses.

20   The personalization server software 305 operates on a computer system which includes one or more high speed processors, data communications capability compatible with the target personalization stations, access to external resources such as security or

13

file servers and a multitasking operating system. The smart card personalization

processes 308, identified as components of the personalization server software 305,

utilize their own virtual memory and share resources as appropriate through threading or

other common techniques well known to one skilled in the art.

5   In summary, the personalization server software moves the processing tasks for

initialization and personalization of smart cards from the personalization station to the

personalization server. The personalization station interface software is responsible for

servicing individual commands from the personalization server software.

    Personalization Software Communication Process. Figure 4 illustrates the

10 communication sequence between the personalization station interface software 304 and

the personalization server software 305 in order to complete personalization of a smart

card. The smart card personalization process begins at stage 402 when the

personalization station interface software 304 receives a unique card object identifier

from the smart card personalization controller as shown in Figure 2. At stage 404, the

15 personalization station interface software 304 requests the commands and data

necessary to personalize the card by passing the card object identifier to the server

software 305. Upon receiving the card object identifier, the server software 305 starts a

personalization session with the personalization station interface software 304 at stage

406.

20   Based on the card object identifier, the server software 305 retrieves and sends

the data and commands unique to the card being personalized to the personalization

station interface software 304 at stage 408. The data and commands are retrieved

14

locally from the smart card personalization server or from additional external data sources as shown in Figure 2 including, for example, the card issuer management system 150.

In one embodiment, the personalization station interface software 304 is idle at stage 410 until it receives the commands and data from the personalization server software 305. Upon receiving the commands and data, the personalization station interface software 304 passes the commands and data directly to the smart card and returns data and/or status signals to the server software 305 as an acknowledgement at stage 412. An example of the data returned by the personalization station interface software 304 is a serial number unique to the card and a random number. The data in such case can be used as part of a function provided by a security service such as an authentication algorithm. At stage 414, the server software 305 processes the status signals and/or data returned by the personalization station interface software 304.

For example, at stage 408 the server software 305 sends a "select" command. The personalization station interface software 304 is idle at stage 410 until it receives the "select" command from the server. At stage 412, the personalization station interface software 304 passes the "select" command on to the smart card and returns a status signal as an acknowledgement to the server software 305. After receiving the acknowledgment at stage 414, the server software 305 sends a "write" command and associated data to the personalization station interface software 304 at stage 408. The personalization station interface software 304 is idle at stage 410 until it receives the "write" command from the server software 305. At stage 412, the personalization

15

station passes the "select" command on to the smart card and returns a status signal as an acknowledgement to the server software 305. The loop from stage 408 to stage 410 to stage 412 to stage 414 continues until the personalization is complete.

Upon completion of the personalization of the smart card, the server software 305 sends a "format complete" command to the personalization station interface software 304 at stage 416. The personalization station interface software 304 is idle at stage 418 until it receives the "format complete" command from the server software 305. At stage 420 the personalization station interface software 304 sends an acknowledgement of the "format complete" command to the server software 305 and to the smart card. The personalization process is complete at stage 422 when the server software 305 receives the acknowledgement.

Conclusion. In summary, the system of the present invention utilizes a personalization server to control smart card personalization in an environment having a plurality of personalization stations. The personalization server provides an interface to a plurality of card personalization stations and to external computing or data resources which normally are not directly available to the card personalization stations or which are not cost efficient to replicate at each card personalization station. The personalization server off-loads the processing of tasks for initialization and personalization of smart cards from the personalization station to the personalization server. The personalization station is responsible for servicing individual commands from the personalization server.

An advantage of the present invention is that the personalization server can

16

support multiple active personalization station sessions. An additional advantage is that the programming logic required in the personalization station is reduced to that of managing data transfers.

Other mechanisms for control of the smart card personalization process will be apparent to those skilled in the art. It is to be understood that the above description is intended to be illustrative, and not restrictive. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.